



an EnerSys® company

Cordex® HP 12kW

Modular Switched Mode Three-Phase Rectifier



- High performance -48V high capacity rectifier for CO, MSC, Data Center and Cable Headend facilities
- High efficiency for decreased OPEX and reduced carbon footprint
- True three-phase, three wire 480VAC input
- Legacy power system upgrade ready, with Cordex® HP controller

Cordex® High-Performance rectifiers make a proven, reliable platform even better, with significant advancements in efficiency and performance.

In a compact, fan-cooled design, Alpha® HP rectifiers open the possibility for immediate OPEX/CAPEX savings, reducing total cost of ownership and impact on the environment, and are useable under a wider range of applications.

The Cordex® HP 12kW is a perfect solution for various 48VDC high capacity applications including Central Office, MTSO's and Data Centers.

Cordex® HP 12kW is a true three-phase, three wire, 480VAC input rectifier which meets the critical requirements of current high density telecommunications environments. It combines the latest DSP controlled power conversion technology, to provide a flexible, efficient and highly reliable DC power source. Local and remote setup, adjustment and control is a simple single-step process with Cordex® CXC HP system controllers. By utilizing TCP/IP technology, complete configuration and monitoring of power equipment is possible through a network web browser.

Cordex® HP 12kW Modular Switched Mode Three-Phase Rectifier

P/N: 0100020-001

Electrical	
Input Voltage:	Nominal: 480VAC (3Ø – 3 Wire + PE) Nominal Range: 430 to 530VAC
Input Frequency:	47 to 63Hz
Current:	17A max
Power:	12,000W
Power Factor:	>0.96% from 50 to 100% load
THD:	<5% from 70 to 100% load
Efficiency:	94.6% Peak
Output Voltage:	42 to 58VDC
Output Current:	220A max
Load Regulation:	Static: <±0.5% Dynamic: <±4% for 40% - 90% load step
Line Regulation:	Static <±0.1%
Noise:	Voice band: <42dBmC Wide band: <20mV RMS (to 10MHz) <150mV pk to pk (to 100MHz)
Psophometric:	<4mV RMS
Acoustic:	<65dBa @ 1m (3ft), 30°C (86°F)
Mechanical	
Dimensions:	mm: 160H x 261W x 326D incl. front panel & handle: 175H x 261W x 364D inches: 6.3H x 10.3W x 11.8D incl. front panel & handle: 7H x 10.3W x 14.4D
Weight:	12.8kg (28lbs)
Shelves	
23" Shelf (2 Modules) P/N: 0300167-001	
Dimensions:	mm: 177H x 530W x 388D inches: 7H x 21.8W x 15.3D
Weight:	11.3kg (25lbs)
Mounting:	Fits 23" racks only flush/center mount
Connections:	Input: Box type terminal block, 3 to 16mm ² (14 to 6AWG) Output: Bus adapters with 3/8" studs on 1" centers Chassis ground: Compression lug, 6 to 16mm ² (10 to 6AWG) CAN communication: RJ 12 offset

Environmental	
Temperature:	Operation: -10 to 65°C (14 to 149°F) full rated power output from 0 to 40°C (32 to 104°F) Storage: -40 to 70°C (-40 to 185°F)
Humidity:	0 to 90% RH non-condensing
Altitude:	-100 to 2000m (-330 to 6560ft)
Heat Dissipation:	<2800 BTU per hour @ 480VAC
Performance / Features	
Indicators:	<ul style="list-style-type: none"> AC mains OK — green LED DC output OK — green LED Module fail — red LED
Controls:	<ul style="list-style-type: none"> CAN interface to CXC-HP Controller
Adjustments (via CXC HP Controller):	<ul style="list-style-type: none"> Float voltage Equalize voltage High voltage alarm Low voltage alarm High voltage shutdown Current limit Slope Start delay timers
Protection:	<ul style="list-style-type: none"> Current limit/short circuit Start delay Input/output fuses Output high voltage shutdown Power limiting
Agency Compliance	
Safety:	CSA C22.2 No 60950-1 UL 60950-1 CE marked IEC/EN 60950-1 CE Marked
EMC:	ETSI 300 386
Emissions:	CFR47 (FCC) Part 15 Class A EN 55022 (CISPR 22) Class A
Immunity:	EN 61000-4-2, 4-3, 4-5, 4-6, 4-11 ANSI / IEEE C62.41 CatB3
NEBS Level 3:	GR-1089 CORE GR-63 CORE



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

09/2020
#047-0259-00 REV B